

65ALR Aluminium Cylinders

Product offering

The 65ALR is a globally approved aluminium cylinder. The 850 litres nominal gas capacity means the cylinder is ideal when larger volumes of gas are required. The cylinder can be supplied with a range of CGA valves designed to meet your specific needs. The cylinder can be filled with both non-reactive and reactive gases.

Characteristic				
	Contents	Typical Fill Pressure	Dimensions	Weight
65ALR	850 Liters	153 bar (2219 psig)	514 mm x 175 mm (20.25" x 6.9")	7.24 kg (16 lb)



Specifications				
	Approvals	Type	Cylinder Valve	Recommended Equipment
65ALR	Global	Refillable Reactive Gases Only	CGA Type. Connection to cylinders varies with gas mixtures required.	Most commonly used regulators include 1000 Series, DFR 2003, or 718 with CGA connection..



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United
Kingdom
+44 1782 566897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 62653788

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com